

Magic extra

Description

Sanitizing washable water-based paint, with a matt appearance, with excellent whiteness and high hiding power. Suitable as a finishing product for remediation and rehabilitation cycles of wall surfaces attacked by biological pests.

Uses

Ideal for all interior surfaces finished with traditional or ready-mix plasters based on gypsum, lime, lime-cement and cement. Particularly indicated for those damp surfaces subject to the formation of mould, such as: bathrooms, kitchens, laboratories, et cetera.

Surface preparation

New walls, or coated with firm paint: plaster, sandpaper, brush, dust and prime with 1 coat of SANAX FISSATIVO appropriately diluted.

Walls treated with low-quality paint or similar: wet the surface with water and scrape, then proceed as for new wall.

Old mouldy surfaces: apply the decontaminating solution BLOCCAMUFFA directly onto the surface with a paintbrush, leave to work for 24 hours, then remove the neutralised mould colonies with a brush. If necessary, remove the old flaking paint, plaster, sandpaper, dust and prime with SANAX FISSATIVO appropriately diluted with water.

In any case, the substrate must be free from saline efflorescences and friable or oily residues.

Application

Apply at least 2 coats of MAGIC EXTRA by brush, roller or spray. Allow at least 10 hours from the primer coat, and at least 8 hours between each coat of paint. Apply at temperatures between 5°C and 30°C. Do not apply on hot or ice-cold surfaces, nor exposed to sun, in presence of strong wind, in imminence of rain or with high relative humidity. Mix well before use.

Dilution

Add 20-25% of water.

Cleaning tools

With water immediately after use.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinara (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015

Storage

24 months in sealed container, away from sources of heat, in a cool and ventilated place, protected from frost.

Technical data

PRODUCT	Breathable sanitizing mural paint
SPECIFIC WEIGHT	1,540 ± 0,050 kg/l
VISCOSITY	10000 ± 2000 cP Brookfield at 23°C
pH	7-9
GLOSS	Matt (<10 g.u. 85°)
HIDING POWER	Class 3
WET SCRUB RESISTANCE	Class 3
COLOUR	White
RECOMMENDED THICKNESS	40-50 dry µm for each coat
RECOMMENDED COATS	2 coats
RECOAT TIME	8-10 hours
APPLICATION METHOD	Brush, roller, spray
THEORETICAL YIELD	4-5 m ² /l for 2 coats
TOUCH-DRY (23°C)	ca. 2 hours
DEEP-DRY (23°C)	18-24 hours

REV 1/2024

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinaro (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015