

LUBENS IMPREGNANTE CERATO

Rev.01/2019

DESCRIPTION

Waxed wood preservative, for interiors and exteriors, based on natural waxes, alkyd resin and phenolic linseed oil. Thanks to its highly penetrative capacity, it is able to restore and protect the surface on which it is applied from algae, fungi and bacteria, without affecting the wood's natural permeability.

USES

It is suitable for coating wood both in marine and mountainous environments. Also used as a base coat in clear, glossy finishes.

PREPARING THE SURFACE:

New wood: Sand with fine sandpaper and remove dust. If necessary degrease with a rag soaked in nitrate thinner.

Already painted wood: Remove existing layers bringing the wood back to new condition, then proceed as for new wood. For damaged surfaces, apply filler, wait until dry, sand to remove the flaws and any excess filler, then dust clean.

In any case, the surface must be dry (not just on the surface, but also in depth) and well seasoned, free from dust, oily and resinous residues, from plant formations, from rot.

APPLICATION

Apply two coats of LUBENS IMPREGNANTE CERATO by brush, roller or spray. Wait at least 14 hours between coats. Always apply two coats of product and three externally. Apply between temperatures of 8°C and 30°C. Avoid application in direct sunlight, on cold or wet surfaces, in the presence of strong wind, if rain is imminent or with high relative humidity. Indoors, ventilate the premises during application. Stir well before use. Test the colour with preliminary tests because the shade is strongly influenced by the wood's original colour.

DILUTION

Add 10%-15% of DILUENTE A for the first coat, and max. 5% of DILUENTE A for successive coats. Stir well before use especially if coloured.

TECHNICAL DATA

PRODUCT	Synthetic wax preservative
SPECIFIC WEIGHT	0.900 ± 0.010 kg/l.
VISCOSITY	15"± 2 DIN Cup 4 at 23° C
COLOUR	Neutral or chart colours
NUMBER OF COATS RECOMMENDED	2-3 coats

RE-COATING

14-16 hours

APPLICATION METHOD

brush, roller or spray

THEORETICAL YIELD:

7-8 sqm/l for two layers

DRYING TIMES (at 23°C)

Touch dry

2-3 hours

Deep dry

24 hours

CLEAN TOOLS

With DILUENTE A immediately after use.

STORAGE

Keep away from heat, in a cool and ventilated place, protected from chills.

The above technical knowledge regarding the application and the proper use of the products does not mean ALCAS ITALIA s.r.l. assumption of responsibility for the use and application of the products. Because of the unpredictable variability of operating conditions, the APPLICATOR must verify the use of the product under their own conditions with direct evidence. We reserve the right to change the contents of this document without prior notice. As soon as a new version of this data sheet is available, it will no longer be valid.