

LUBENS PROTETTIVO SATINATO

Rev.01/2019

DESCRIPTION

Transparent protective satin wood coating for exteriors and interiors. Its unique composition provides high resistance to external aggressive agents and excellent paint film distension. Easy to apply, non-yellowing and UV-resistant.

USES

It is suitable for the coating of wood in marine environments. It is also suitable for a fine finish of fixtures and furnishing products.

PREPARING THE SURFACE

New wood: Sand with fine sandpaper and remove dust. If necessary degrease with a rag soaked in nitrate thinner. For better protection of the wood and better anchoring, apply one or two primer coats of neutral or coloured LUBENS IMPREGNANTE.

Already painted wood: Remove existing layers bringing the wood back to new condition, then proceed as for new wood.

For damaged surfaces, apply filler, wait until dry, sand to remove the flaws and any excess filler, then dust clean.

In any case, the surface must be dry (not just on the surface, but also in depth) and well seasoned, free from dust, oily and resinous residues, from plant formations, from rot.

APPLICATION

Apply 2 to 3 coats of LUBENS PROTETTIVO SATINATO by brush, roller or spray. Wait at least 18 hours between coats. To get a perfect finish sanding with fine paper between one coat and the other is recommended.

Apply between temperatures of 5°C and 30°C. Avoid application in direct sunlight, on cold or wet surfaces, in the presence of strong wind, if rain is imminent or with high relative humidity. Indoors, ventilate the premises during application. Stir well before use.

DILUTION

5-10% in weight with DILUENTE A. Stir well before use.

TECHNICAL DATA

PRODUCT	Synthetic clear varnish
SPECIFIC WEIGHT	0.940 ± 0.010 kg/L.
VISCOSITY	250 ± 50 Brookfield cPs at 23°C
GLOSS	Gloss (60 °): 43 ± 2
COLOUR	Neutral

RECOMMENDED THICKNESSES	35÷40 dry microns per coat
NUMBER OF COATS RECOMMENDED	2 coats
RE-COATING	18-24 hours
APPLICATION METHOD	brush, roller or spray
THEORETICAL YIELD:	8-10 sqm/l for two layers
DRYING TIMES (at 23°C)	
Touch dry	2-3 hours
Deep dry	24 hours

CLEAN TOOLS

With DILUENTE A immediately after use.

STORAGE

Keep away from heat, in a cool and ventilated place, protected from chills.

The above technical knowledge regarding the application and the proper use of the products does not mean ALCAS ITALIA s.r.l. assumption of responsibility for the use and application of the products. Because of the unpredictable variability of operating conditions, the APPLICATOR must verify the use of the product under their own conditions with direct evidence. We reserve the right to change the contents of this document without prior notice. As soon as a new version of this data sheet is available, it will no longer be valid.