

ALCASABLE SOFT

Rev.01/2019

DESCRIPTION

Decorative water based paint for interiors, pearlescent, easy to apply. Its particular composition, based on acrylic copolymers, selected particle size fillers and special additives, gives the product unique and bright sand reflections. It is offered in three finishes - PEARL, GOLD, and COPPER.

USES

For its outstanding chromatic effect it is particularly suited for embellishing the interiors of apartments, studios, villas, hotels, and any other environments that require unique and prestigious finishes.

PREPARING THE SURFACE

Make sure the surface is perfectly dry, clean and smooth and well-seasoned. Check that any existing paint is perfectly anchored to the surface. Having prepared the surface, apply with a brush or short hair roller, one or two coats of ISOLCOPREX INTERIOR the first diluted with 50-100% water and the second with 20-30% water, preferably of the same shade as ALCASABLE PEARL. Wait at least 6 hours between coats. After at least 12 hours apply ALCASABLE SOFT.

APPLICATION

Apply by brush, working with alternated and crossed strokes and taking care to avoid accumulations, a coat of ALCASABLE SOFT diluted with max 10% of water. After approximately 4 hours apply the second coat, diluted with max. 10% water, with the same technique. In the first drying phase wipe the discharged brush in order to guide the particles and obtain the desired design and effect. The application temperature should be between 5°C and 30°C.

The product can be cleaned with a soft sponge using water and common soaps and neutral detergents. Do not use detergents and alcohol solvents.

In order to achieve the described decorative effects it is essential to use ISOLCOPREX INTERIOR as the base.

DILUTION

Add at most 10% of water.

TECHNICAL DATA

PRODUCT	Decorative finish
SPECIFIC WEIGHT	1.140 ± 0.050 kg /L
VISCOSITY	5000± 1000 Brookfield cPs at 23°C
pH	7-9

COLOUR

NUMBER OF COATS RECOMMENDED

APPLICATION METHOD

THEORETICAL YIELD:

DRYING TIME (at 23 ° C)

Tack

Touch dry

Deep dry

Chart colors

2 coats

Paint brush

8-10 sq.m/L for 2 layers

About 1 hour

3-4 hours

24 hours

CLEAN TOOLS

With water immediately after use.

STORAGE

Keep away from heat, in a cool and ventilated place, protected from chills.

The above technical knowledge regarding the application and the proper use of the products does not mean ALCAS ITALIA s.r.l. assumption of responsibility for the use and application of the products. Because of the unpredictable variability of operating conditions, the APPLICATOR must verify the use of the product under their own conditions with direct evidence. We reserve the right to change the contents of this document without prior notice. As soon as a new version of this data sheet is available, it will no longer be valid.