

BLOCCAMUFFA

Rev.01/2019

DESCRIPTION

Special solution to clean surfaces that are attacked by mould, algae and moss. It is essential when it is intended to repaint or cover supports damaged by the aggression of algae, as it stops the proliferation of the latter that, with any other type of treatment, they would be able to survive, in the form of spores, even with the application of sanitizing products. Therefore, within a sanitizing cycle, this product is destined to be the first to be used.

USES

Ideal as a pre-treatment for all cases where the surface has been attacked by microorganisms.

PREPARING THE SURFACE

In cases where surface has traces of mould or fungus no mechanical action is recommended before applying the solution, since it would result in a spread of spores that would go to attack other, perhaps uncontaminated, parts of the walls. It is therefore recommended to use the solution directly on contaminated surfaces. If applied indoors, ventilate well during and after use of BLOCCA MUFFA. Allow the sanitising solution to work for 24 hours and then vigorously clean the inert mould residues.

APPLICATION

Apply one coat of BLOCCA MUFFA by brush or roller. Apply between temperatures of 5 and 30 ° C. Do not apply on surfaces that are in direct sunlight, hot or cold, or in the presence of strong wind, if rain is imminent or in the presence of high relative humidity. Stir well before use.

DILUTION

Ready to use.

TECHNICAL DATA

PRODUCT	Tempering detergent
SPECIFIC WEIGHT	1.000 ± 0.01 kg /l.
VISCOSITY	Liquid
COLOUR	Colourless
NUMBER OF COATS RECOMMENDED	1 coat
RE-COATING	24-48 hours
APPLICATION METHOD	Brush, roller
THEORETICAL YIELD	10-12 sqm /l for 1 layer
DRYING TIME (at 23°C)	
Touch dry	Around 2 hours

Deep dry

18-24 hours

CLEAN TOOLS

With water immediately after use.

STORAGE

Keep away from heat, in a cool and ventilated place, protected from chills.

The above technical knowledge regarding the application and the proper use of the products does not mean ALCAS ITALIA s.r.l. assumption of responsibility for the use and application of the products. Because of the unpredictable variability of operating conditions, the APPLICATOR must verify the use of the product under their own conditions with direct evidence. We reserve the right to change the contents of this document without prior notice. As soon as a new version of this data sheet is available, it will no longer be valid.