

# SANAX

Rev.01/2019

## DESCRIPTION

Highly washable water-based paint, anti-mould and sanitising for interiors with particular aesthetic and protective characteristics. Its special formulation gives it excellent coverage, high whiteness, a good matte finish, strong washing and alkali resistance. Its anti-mould action means that, as well as blocking the life of the microorganisms already present in the walls, it also prevents the proliferation of new moulds. It is most important when, creating a sanitizing cycle, one does not want to lose the pleasantness of an opaque and velvety finish.

## USES

SANAX is recommended for all environments that require maximum hygiene. Suitable against any attack by moulds and fungi, it can be used both in environments where there is development of moisture and organic residues (dairy/meat factories, pools, bakeries, wineries) as well as in residential buildings, especially in damp and poorly ventilated spaces.

## PREPARING THE SURFACE

New surfaces: apply a layer of properly diluted SANAX FISSATIVO after adequate surface preparation.

Old mouldy surfaces: Apply the disinfectant BLOCCA MUFFA directly on the surface with a brush, leave the sanitising solution for 24 hours and vigorously remove the now inactive mould colonies with a brush. If you need to remove flaking old paint, fill, sand, dust and impress with SANAX FISSATIVO diluted with water.

In any case, the surface must be free from efflorescence, loose and oily residues and well-seasoned (at least 4-6 weeks) also for new patches which may have been applied.

## APPLICATION

Apply two coats of SANAX by brush or wool roller. Allow at least 10 hours after the primer and at least 8 hours between the first and second coat of paint. Application temperatures must be between 5°C and 30°C. Do not apply to hot or cold surfaces, in the presence of strong winds, in environments where the humidity exceeds 80%.

## DILUTION

Add 30-35% water.

## TECHNICAL DATA

**PRODUCT**  
**SPECIFIC WEIGHT**  
**VISCOSITY**

Super-washable anti-mould paint  
1.420 ± 0.050 kg /L  
20000 ± 2000 Brookfield cPs at 23°C

<b>pH</b>	7-9
<b>GLOSS</b>	Opaque <10 G.U. 85°
<b>COVERING CAPACITY</b>	Class 2
<b>WET ABRASION RESISTANCE</b>	Class 2
<b>COLOUR</b>	White
<b>RECOMMENDED THICKNESSES</b>	30÷40 dry microns per coat
<b>NUMBER OF COATS RECOMMENDED</b>	2 coats
<b>RE-COATING</b>	8-10 hours
<b>APPLICATION METHOD</b>	Brush, roller
<b>THEORETICAL YIELD:</b>	7-9 sqm /l for two layers
<b>DRYING TIMES (At 23°C)</b>	
<b>Touch dry</b>	Around 2 hours
<b>Deep dry</b>	18-24 hours

#### **CLEAN TOOLS**

With water immediately after use.

#### **STORAGE**

Keep away from heat, in a cool and ventilated place, protected from chills.

The above technical knowledge regarding the application and the proper use of the products does not mean ALCAS ITALIA s.r.l. assumption of responsibility for the use and application of the products. Because of the unpredictable variability of operating conditions, the APPLICATOR must verify the use of the product under their own conditions with direct evidence. We reserve the right to change the contents of this document without prior notice. As soon as a new version of this data sheet is available, it will no longer be valid.