

# DILUENTE A

Rev.01/2019

## DESCRIZIONE

Diluent formulated with aliphatic hydrocarbons. It is used for the dilution of synthetic paint and varnish for brush applications. The absence of aromatic solvents ensures low odour and reduced harmfulness. It can also be used for cleaning spray guns, paint brushes and equipment soiled with paint. Due to its characteristics of purity, the product is stable and does not deteriorate.

## CAMPI DI IMPIEGO

Dilution: dilute the coating product until the desired viscosity is reached: an optimal dilution will enhance gloss and lay of the paint.

Cleaning: use for the cleaning of surfaces, brushes and spray guns soiled with paint.

**Important:** always carry out a preliminary test before using.

Use the product in accordance with good working practices, avoiding the dispersion of the product or the packaging in the environment.

## DATI TECNICI

<b>PRODUCT</b>	Syntetic diluent
<b>SPECIFIC WHEIGHT</b>	0,790 ± 0,010 Kg/lt
<b>PHYSICAL STATE</b>	Liquid
<b>COLOUR</b>	Colourless
<b>ODOUR</b>	Characteristic
<b>WATER SOLUBILITY</b>	Immiscible with water

## STOCCAGGIO

24 months in sealed packaging, away from heat sources, in a cool and ventilated place, repaired from frost.

The above technical knowledge regarding the application and the proper use of the products does not mean ALCAS ITALIA s.r.l. assumption of responsibility for the use and application of the products. Because of the unpredictable variability of operating conditions, the APPLICATOR must verify the use of the product under their own conditions with direct evidence. We reserve the right to change the contents of this document without prior notice. As soon as a new version of this data sheet is available, it will no longer be valid.