

ALCADECOR

Rev.01/2019

DESCRIPTION

Decorative easy to apply water-based stucco paste for interior applications. The special composition, based on grassello di calce and selected raw materials, gives the treated wall surface a shiny, soft, breathable and a very elegant effect, reminiscent of classic stucco found in the ancient Venetian stately buildings.

Applicable on new and old water-based plasters, concrete, plaster and drywall surfaces, old painted surfaces and coatings that are organic or mineral in nature, dry, compact, absorbent and cohesive, of various mineral based conglomerates. The particularly elegant finish and brightness, are give the environments in which it is applied a better brightness enhancing the context of the furniture.

USES

Given the variety of shades and effects obtainable, it is particularly suitable for embellishing the interior surfaces of apartments, studios, villas, hotels, and other settings which require finishes that combine modernity and elegance with extraordinary visual and tactile aesthetic effect.

PREPARING THE SURFACE

Make sure the surface is perfectly dry and well-seasoned, devoid of grease, oil and other contaminants, free of holes, cracks and fissures. In case of degraded surfaces, by brushing or washing, remove all traces of old flaking paint and any saline efflorescence. Completely remove flaking layers of lime or tempera painting. In the presence of mould or algae, apply specific treatment. In the case of new powdery or highly absorbent plaster, on filled areas or old powdery paints, apply one coat of insulating fixative to achieve uniform surface absorption, such as appropriately diluted CLK. Check that any existing paint is perfectly anchored to the surface. Having adequately prepared the surface, then apply with a brush or short-hair roller, one-two coats of ISOLCOPREX INTERIOR primer, the first coat diluted with 50-100% water and the second with 20-30% water. Wait at least 6 hours between primer coats. After at least 12 hours, apply ALCADDECOR.

APPLICATION

24 hours before application, it is advisable to machine-stir until an even and uniform colour is achieved. Spread and smooth, with a stainless steel trowel, one or more layers of ALCADDECOR until a smooth and uniform surface is achieved. Wait at least 5 hours between layers, always sand with fine sandpaper and dust well. For the finishing coat apply a further layer of ALCADDECOR with a steel spatula. Apply a small amount of product and at a time and spread the material, overlaying the brushstrokes with rapid and decisive movements. Depending on the desired visual effect, make spatula strokes of greater or lesser width. After 10-15 minutes, pass the spatula several times with semicircular movements, pressing gently until a shiny appearance is achieved. An important device to easily obtain a pleasantly glossy effect consists in stirring ALCADDECOR (before

the top coat) to make it more liquid. It will thus penetrate more easily into every crack and with a light application pressure, the surface will become smooth.

It is advisable to perform the finishing process on small area segments (approx. 1 sq.m). When moving onto the next area, take care to overlap the edges to avoid any signs of discontinuity.

The application temperature should be between 8 °C and 35 °C. The product can be cleaned with a non-abrasive sponge using water and common soaps and neutral detergents. Do not use alcohol and solvent-based detergents.

*In order to achieve the described decorative effect, **it is essential** to use ISOLCOPREX INTERIOR as a primer base. After application a protective waxing should be applied.*

DILUTION

Ready for use.

TECHNICAL DATA

PRODUCT	Decorative finishing
SPECIFIC WEIGHT	1.530 ± 0.050 kg/L
VISCOSITY	Thick paste
COLOUR	White and chart colours
APPLICATION METHOD	Stainless steel trowel and spatula
THEORETICAL YIELD	1-1.3 kg/sq.m for three layers on plaster 0.4-0.6 kg/sq.m for three layers on smooth surfaces (plaster, plasterboard, etc.).
DRYING TIME (at 23 °C)	
Dust-free time	30-40 minutes
Touch dry	2-3 hours
May be sanded and recoated	after 5 hours
Deep dry	24 hours

CLEANING

Whit water immediately after use.

STORAGE

Keep away from heat, in a cool and ventilated place, protected from freezing temperatures.

The above technical knowledge regarding the application and the proper use of the products does not mean ALCAS ITALIA s.r.l. assumption of responsibility for the use and application of the products. Because of the unpredictable variability of operating conditions, the APPLICATOR must verify the use of the product under their own conditions with direct evidence. We reserve the right to change the contents of this document without prior notice. As soon as a new version of this data sheet is available, it will no longer be valid.