

REAL STONE

Rev.01/2019

DESCRIPTION

Protective transparent waterproofing coating, water-dilutable and easy to apply.

The special composition gives the product remarkable properties:

It impregnates and protects the treated material in depth without altering its breathability;

It protects the material surface from weather degradation; it creates a barrier against water and oil stains; it reduces the material's absorption capacity without altering its aesthetic qualities; it does not form a superficial film and creates a pleasant natural effect.

USES

It is used as a protective water repellent for external paving tiles, natural stone, marble, granite, agglomerates and concrete. For indoor flooring, it is used as the base for the first protective wax layer. It is ideal for interior and exterior walls.

PREPARING THE SURFACE

The surface to be protected must be free from dirt, dust and traces of oil and grease. The surface maybe treated even if it is not perfectly dry.

APPLICATIONS

It can be applied by brush or roller.

For external paving: shake well before use and after appropriate dilution, apply a first coat with a flat brush, spreading the product evenly without creating any surface pools – this is particularly important for less absorbent materials.

Depending on the absorption characteristics of the surface, apply two or three coats within a few hours of each other - as soon as the surface is dry the next coat may be applied.

On Tuscan "cotto" tiling or low absorbency stonework, two coats will be required; on very absorbent tiling or very porous stonework and concrete, at least three coats will be needed. If using as a primer, simply apply one coat.

For indoor flooring: shake well before use and after appropriate dilution apply a coat of the product with a flat brush.

The temperature of both the environment and the surface should be between 10 and 30 °C.

DILUTION

Depending of the surface porosity, thin the first coat with 50-100% water. Apply the following coats in the same manner.

TECHNICAL DATA

PRODUCT	Waterproofing protective coating
SPECIFIC WEIGHT	0.960 ± 0.010 kg/L.
pH	7-9
GLOSS	Matt
COLOUR	Clear
RECOMMENDED THICKNESS	10÷20 microns per dry coat
NUMBER OF COATS RECOMMENDED	2 coats
RE-COATING	8-10 hours
APPLICATION METHOD	Brush, roller or spray
THEORETICAL YIELD	10-15 sq.m/L for 2 layers
DRYING TIME (at 23 °C)	
Dust-free time	30-60 minutes
Touch dry	1-2 hours
Deep dry	4-6 hours

CLEANING TOOLS

With water immediately after use.

STORAGE TEMPERATURE

The product should be stored tightly closed at temperatures between 5 and 30 °C. Protect from freezing temperatures.

For open containers, exposure to air and moisture must absolutely be avoided.

The above technical knowledge regarding the application and the proper use of the products does not mean ALCAS ITALIA s.r.l. assumption of responsibility for the use and application of the products. Because of the unpredictable variability of operating conditions, the APPLICATOR must verify the use of the product under their own conditions with direct evidence. We reserve the right to change the contents of this document without prior notice. As soon as a new version of this data sheet is available, it will no longer be valid.