

FUMOFIX

Description

Semi-covering water-based stain-resistant primer for interiors and exteriors. Produced with resinous microemulsions which guarantee its high penetration capacity even on compact supports, as well as a strong consolidating power even on particularly absorbent and chalky surfaces. Suitable for all types of substrates, such as: different types of plaster, cement, brick, concrete, plaster and old coatings or paints.

Uses

Suitable for the treatment of all those surfaces where it is necessary to create a barrier against soot, smoke, nicotine and blackening, avoiding surface surfacing.

Surface preparation

Brush, wash and scrape well, removing any non-adherent parts, fill, and then proceed with the application of FUMOFIX.

In any case, the support must be perfectly dry, free from salt efflorescence, oily residues, mold and well cured even in any new patches made.

Application

Apply 1 coat of FUMOFIX, ready for use, with a brush or roller. Wait until the product is completely dry and after 4-6 hours proceed with installing the SMOKE COVER product. Apply at temperatures between +5 and +30°C. Do not apply on sunny, hot or freezing surfaces, in the presence of strong winds, in the imminent presence of rain or in the presence of high relative humidity. Mix well before use.

Dilution

Ready to use.

Cleaning tools

With water immediately after use.

Storage

Keep away from sources of heat, in a cool and ventilated place, repaired from frost.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinara (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015

Technical data

PRODUCT	Ultrafine mural fixative primer
SPECIFIC WEIGHT	1,00 ± 0,01 kg/l at 20°C
RECOMMENDED THICKNESS	1 coat
RECOAT TIME	4-6 hours
APPLICATION METHOD	Brush, roller
THEORETICAL YIELD	12-16 m ² /l for 1 coat
TOUCH-DRY (23°C)	1-2 hours
DEEP-DRY (23°C)	18-24 hours

REV 1/2024

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinara (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015