

# Alcasable

## Description

Water-based indoor decorative paint, pearlescent, easy to apply. The particular composition, based on acrylic copolymers, fillers with selected particle size and special additives, provides exclusive and bright reflections together with the scratched appearance due to the presence of sand. It is available in three different bases: PEARL, GOLD, RAME.

## Uses

For its extraordinary chromatic effect, it is particularly indicated for embellishing interior surfaces of flats, studies, villas, hotels and any other environment requiring a unique, valuable finish.

## Surface preparation

Ensure that the substrate is perfectly dry and seasoned, clean and smooth. Test for proper adhesion of existing paint. Once the substrate has been prepared, apply (by brush or short-pile roller) 2 coats of ISOLCOPREX INTERIOR (the 1<sup>st</sup> one diluted with 50-100% of water, the 2<sup>nd</sup> one with 20-30% of water), preferably colour-matched with the chosen shade of ALCASABLE. Allow at least 6 hours between each coat. After at least 12 hours, apply ALCASABLE.

## Application

Apply with a paddle brush (crossing the strokes and avoiding product excess) 1 coat of ALCASABLE diluted with max. 5% of water. As soon as the applied product starts drying, run the discharged brush over the surface, so as to arrange the sand particles according to the desired effect.

The temperature of application must be between 5°C e 30°C. The product can be wiped with a non-abrasive sponge, using water and ordinary neutral soaps and detergents. Do not use alcoholic detergents or solvents.

**In order to obtain the aforesaid decorative effect, it is essential to employ ISOLCOPREX INTERIOR as an undercoat.**

## Dilution

Add max. 5% of water.

## Cleaning tools

With water immediately after use.

### Alcas Italia srl

head office  
via A. Moro, 29  
81031 Aversa (CE)  
PI 03613710619  
SDI 5RU082D

production plant  
Zona Asi Aversa Nord  
81032 Carinaro (CE)  
T +39 081 502 6184  
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management  
systems  
UNI EN ISO 9001:2015

Certified organization



Environmental management  
systems  
UNI EN ISO 14001:2015

## Storage

24 months in sealed container, away from sources of heat, in a cool and ventilated place, protected from frost.

## Technical data

PRODUCT	Decorative coating
SPECIFIC WEIGHT	1,140 ± 0,050 kg/l
VISCOSITY	8000 ± 2000 cP Brookfield at 23°C
pH	7-9
COLOUR	<i>Palette</i> hues
RECOMMENDED THICKNESS	40-50 dry µm for each coat
RECOMMENDED COATS	1 coat
APPLICATION METHOD	Paddle brush
THEORETICAL YIELD	7-8 m <sup>2</sup> /l for 2 coats
DUST-FREE TIME	ca. 1 hour
TOUCH-DRY (23°C)	3-4 hours
DEEP-DRY (23°C)	24 hours

## REV 1/2023

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

### Alcas Italia srl

head office  
via A. Moro, 29  
81031 Aversa (CE)  
PI 03613710619  
SDI 5RU082D

production plant  
Zona Asi Aversa Nord  
81032 Carinaro (CE)  
T +39 081 502 6184  
info@alcasitalia.it | [www.alcasitalia.it](http://www.alcasitalia.it)

Certified organization



Quality management  
systems  
UNI EN ISO 9001:2015

Certified organization



Environmental management  
systems  
UNI EN ISO 14001:2015