

# Alcasan

## Description

Special sanitizing additive that, added into traditional emulsion paints, makes the film resistant towards the aggression of mould and algae. Its particular components make it an essential enhancement for those products that are intended to be applied in environments subject to biological attack. Thanks to its wash resistance, it ensures prolonged effectiveness over time.

## Uses

Indicated for indoor and outdoor mural paints and coatings.

## Application

Add 250 ml of additive in 7-14 litres of mural paint or coating. Mix well before use.

## Cleaning tools

With water immediately after use.

## Storage

24 months in sealed container, away from sources of heat, in a cool and ventilated place, protected from frost.

## Technical data

PRODUCT	Sanitizing additive
SPECIFIC WEIGHT	1,000 ± 0,005 kg/l

### REV 1/2023

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

### Alcas Italia srl

head office  
via A. Moro, 29  
81031 Aversa (CE)  
PI 03613710619  
SDI 5RU082D

production plant  
Zona Asi Aversa Nord  
81032 Carinara (CE)  
T +39 081 502 6184  
info@alcasitalia.it | [www.alcasitalia.it](http://www.alcasitalia.it)

Certified organization



Quality management  
systems  
UNI EN ISO 9001:2015

Certified organization



Environmental management  
systems  
UNI EN ISO 14001:2015