

# CLK

## Description

Waterborne indoor/outdoor consolidating mural primer. Produced with resin microemulsions which provide high permeating power even on compact substrates and a strong consolidating power even on particularly absorbent and chalking surfaces. Suitable for multiple types of substrates, such as: plasters of various kinds, cement, masonry, concrete, gypsum and old coatings and paints. It can also be employed in external wall insulations systems.

## Uses

Suitable for use on surfaces which require consolidation, uniformity of absorption and good adhesion with the paintwork.

## Surface preparation

New substrates: brush and dust until all friable residues are removed.

Painted substrates: brush and scrape in order to remove peeling parts; plaster, then apply CLK appropriately diluted.

In any case, the substrate must be perfectly dry, free from saline efflorescences, oily residues and mould, and properly seasoned (at least 4-6 weeks), including any recent restoration patch.

## Application

Apply 1 coat of CLK, appropriately diluted, by brush or roller. Wait for the product to dry and, after 4-6 hours, apply the top finish coating. If overpainted with COPRIFUMO, dilute CLK with 100% of water. Apply at temperatures between 5°C and 30°C. Do not apply on hot, ice-cold surfaces or exposed to sun, in presence of strong wind, in imminence of rain or in presence of high relative humidity. Mix well before use.

## Dilution

Add 300-400% of water.

## Cleaning tools

With water immediately after use.

## Storage

Keep away from sources of heat, in a cool and ventilated place, repaired from frost.

### Alcas Italia srl

head office  
via A. Moro, 29  
81031 Aversa (CE)  
PI 03613710619  
SDI 5RU082D

production plant  
Zona Asi Aversa Nord  
81032 Carinaro (CE)  
T +39 081 502 6184  
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management  
systems  
UNI EN ISO 9001:2015

Certified organization



Environmental management  
systems  
UNI EN ISO 14001:2015

## Technical data

|                       |                                    |
|-----------------------|------------------------------------|
| PRODUCT               | Ultrafine mural fixative primer    |
| SPECIFIC WEIGHT       | 1,00 ± 0,01 kg/l at 20°C           |
| RECOMMENDED THICKNESS | 1 coat                             |
| RECOAT TIME           | 4-6 hours                          |
| APPLICATION METHOD    | Brush, roller                      |
| THEORETICAL YIELD     | 30-50 m <sup>2</sup> /l for 1 coat |
| TOUCH-DRY (23°C)      | 1-2 hours                          |
| DEEP-DRY (23°C)       | 18-24 hours                        |

### REV 1/2023

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

### Alcas Italia srl

head office  
via A. Moro, 29  
81031 Aversa (CE)  
PI 03613710619  
SDI 5RU082D

production plant  
Zona Asi Aversa Nord  
81032 Carinara (CE)  
T +39 081 502 6184  
info@alcasitalia.it | [www.alcasitalia.it](http://www.alcasitalia.it)

Certified organization



Quality management  
systems  
UNI EN ISO 9001:2015

Certified organization



Environmental management  
systems  
UNI EN ISO 14001:2015