



Diluente S

Description

Formulated with selected raw materials, it is used for the dilution of synthetic and oleosynthetic enamel paints and varnishes. The absence of aromatic solvents ensures low odour and reduced harmfulness. Also employable for cleaning spray guns, brushes and tools soiled with solventborne paints. For its characteristics of purity, the product is stable and does not deteriorate.

Uses

For diluting: thin the coating product down to the desired viscosity; optimal dilution enhances paint gloss and levelling.

For cleaning: use as a solvent for reclaiming surfaces, brushes and spray guns soiled with solventborne coatings.

Important: always perform preliminary tests before use.

Employ the product according to best work practices, avoiding the dispersion of the product or the container in the environment.

Storage

24 months in sealed container, away from sources of heat, in a cool and ventilated place, protected from frost.

Technical data

PRODUCT	Synthetic paint thinner
SPECIFIC WEIGHT	0,790 ± 0,010 kg/l
PHYSICAL STATE	Liquid
COLOUR	Colourless
ODOUR	Characteristic
HYDROSOLUBILITY	Immiscible with water

REV 1/2023

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

1

Alcas Italia srl

head office via A. Moro, 29 81031 Aversa (CE) 81032 Carinaro (CE) PI 03613710619 SDI 5RUO82D

production plant Zona Asi Aversa Nord T+39 081 502 6184 info@alcasitalia.it | www.alcasitalia.it



Cert



Quality management systems UNI EN ISO 9001:2015 Environmental management systems

UNI EN ISO 14001:2015