

Glitter Diamond

Description

GLITTER DIAMOND is a special toner based on particular waterborne copolymers and shiny, sparkling, 3D-effect coloured flakes, with excellent colourfastness and brightness. Added to products such as paints, decorative coatings and water-based protective varnishes, it creates a bright, shiny surface that embellishes the finishes by amplifying and reflecting light.

Available versions: ORO (*gold*), ARGENTO (*silver*) and ARGENTO OLOGRAFICO (*holographic silver*).

Uses

For the extraordinary bright effect, it is particularly indicated for decorating interior surfaces of flats, villas, hotels and any other environment requiring peculiar, shiny finishes.

Application

GLITTER DIAMOND can be poured directly into products with moderate viscosity (such as emulsion paints and waterborne enamel paints), taking care to mix adequately.

Apply at temperatures between 5°C and 30°C. Do not apply on hot or ice-cold surfaces, in presence of strong ventilation, in environments with high relative humidity.

Dilution

Ready to use. Stir exclusively by hand before use.

Cleaning tools

With water immediately after use.

Storage

24 months in sealed container, away from sources of heat, in a cool and ventilated place, protected from frost.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinara (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015

Technical data

PRODUCT	Paint additive (glitter)
SPECIFIC WEIGHT	1,000 ± 0,010 kg/l at 20°C
VISCOSITY	Viscous liquid
COLOUR	Gold, silver, holographic silver
APPLICATION METHOD	Brush, roller
THEORETICAL YIELD	1 jar (200 ml) for 2-3 litres of product

REV 1/2023

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

2

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinaro (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015