

Maxima

Description

Waterborne paint with high coverage and good permeability to vapour.

Uses

Particularly indicated for interior environments that require good breathability.

Surface preparation

New walls: plaster, sandpaper, dust and prime with ALCAFIX appropriately diluted with water.

Treated interior walls: remove existing paint or any flaking part as much as possible, plaster, sandpaper, dust and then prime with ALCAFIX appropriately diluted.

In any case, the substrate must be perfectly dry and well seasoned, free from saline efflorescences, oily residues, plant formations, bacterial colonies.

Application

Apply at least 2 coats of MAXIMA by brush, roller or spray. Allow at least 12 hours from the primer coat, and at least 8 hours between the 1st and the 2nd coat of paint. Apply at temperatures between 5°C and 30°C. Mix well before use.

Dilution

Add 15-25% of water.

Cleaning tools

With water immediately after use.

Storage

24 months in sealed container, away from sources of heat, in a cool and ventilated place, protected from frost.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinaro (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015

Technical data

PRODUCT	Waterborne paint
SPECIFIC WEIGHT	1,640 ± 0,050 kg/l
VISCOSITY	18000 ± 2000 cP Brookfield at 23°C
pH	7-9
GLOSS	Matt (<10 g.u. 85°)
HIDING POWER	Class 3
WET SCRUB RESISTANCE	Class 5
COLOUR	White
RECOMMENDED THICKNESS	40-50 dry µm for each coat
RECOMMENDED COATS	2 coats
RECOAT TIME	8-10 hours
APPLICATION METHOD	Brush, roller, spray
THEORETICAL YIELD	4-5 m ² /l for 2 coats
TOUCH-DRY (23°C)	1-2 hours
DEEP-DRY (23°C)	18-24 hours

REV 2/2023

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinaro (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015