

Plastiver

Description

Solution formulated for the production of professional mural plaster. It enhances the adhesion of the plaster to the substrate and improves plasticity, sandpapering easiness and final mechanical resistance.

Uses

For indoor environments, ceilings and walls.

Preparation

Mix 1 part of product with 1 part of selected fillers with a mechanical tool at low r.p.m., slowly sprinkling the powders onto the solution until a uniform mixture is obtained. In order to further improve plasticity and sandpapering easiness, add 10-20% of water to the mixture.

Application

With a finishing trowel.

Dilution

Ready to use.

Cleaning tools

With water, immediately after use.

Storage

24 months in sealed container, away from sources of heat, in a cool and ventilated place, repaired from frost.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinara (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015

Technical data

PRODUCT	Liquid vehicle for powder plasters
SPECIFIC WEIGHT	1,000 ± 0,010 kg/l
VISCOSITY	Thixotropic viscous paste
RECOMMENDED THICKNESS	500-600 µm
RECOMMENDED COATS	1-2 coats
RECOAT TIME	24 hours
APPLICATION METHOD	Finishing trowel
POT LIFE (23°C)	1-2 hours
THEORETICAL YIELD	1-2 kg/m ² for a 500-600 µm layer
TOUCH-DRY (23°C)	2-4 hours
SANDPAPERING (23°C)	After at least 6 hours

REV 1/2023

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinara (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015