

Sanax Fissativo

Description

Antimould mural fixative primer based on special microemulsions that provide high penetrating and consolidating power. Thanks to its antimould properties, it is particularly indicated for priming and consolidating surfaces to be treated with antimould sanitizing paints.

Uses

Treatment of all those surfaces that require consolidation and preparation for proper adhesion and even absorption of the new paint, enhancing the finish and the yield of the application.

Surface preparation

Remove flaking parts, efflorescences, dust, traces of oil, grease and other contaminants. Flatten out, plaster if necessary, then proceed with the application of the primer.

In any case, the substrate must be perfectly dry and seasoned (at least 4-6 weeks) including any recent restoration patch.

Application

Apply 1 coat of SANAX FISSATIVO by brush or roller. Apply at temperatures between 5°C and 30°C. Do not apply on hot or ice-cold surfaces, nor exposed to sun, in presence of strong wind, in imminence of rain or with high relative humidity. Mix well before use.

Dilution

Add 300-400% of water.

Cleaning tools

With water immediately after use.

Storage

24 months in sealed container, away from sources of heat, in a cool and ventilated place, protected from frost.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinaro (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015

Technical data

PRODUCT	Antimould fixative primer
SPECIFIC WEIGHT	1,000 ± 0,010 kg/l
RECOMMENDED COATS	1 coat
RECOAT TIME	10-12 hours
APPLICATION METHOD	Brush, roller
THEORETICAL YIELD	30-50 m ² /l for 1 coat
TOUCH-DRY (23°C)	1-2 hours
DEEP-DRY (23°C)	18-24 hours

REV 1/2023

The aforementioned technical notions regarding the application and correct use of the product do not imply liability of Alcas Italia S.r.l. for use and application of the products themselves. Due to the unpredictable variability of application conditions, the USER must verify with direct tests the suitability of the product for each peculiar use. We reserve the right to modify the content of this document, without notification. As soon as a new version of these technical data sheet becomes available, this one won't be valid any longer.

Alcas Italia srl

head office
via A. Moro, 29
81031 Aversa (CE)
PI 03613710619
SDI 5RU082D

production plant
Zona Asi Aversa Nord
81032 Carinaro (CE)
T +39 081 502 6184
info@alcasitalia.it | www.alcasitalia.it

Certified organization



Quality management
systems
UNI EN ISO 9001:2015

Certified organization



Environmental management
systems
UNI EN ISO 14001:2015